



Electric light commercial water heater
EES - 120/150/190/300 & 455 L



**WHY PEOPLE PREFER AN
A. O. SMITH WATER HEATER...**

ADVANCED TECHNOLOGY

ENERGY SAVING

SUPERIOR QUALITY

MADE BETTER



EES

Electric light commercial water heater

KEY FEATURES



BLUE DIAMOND® GLASS LINING
Blue Diamond® Glass Lined Tank. Maximum protection against hard water and corrosion.



GLASS COATED HEATING ELEMENT
Helps to prevent scale formation and extends the life of the heating element.



TEMPERATURE CONTROL KNOB
Allows you to set the temperature anywhere between 25°C to 75°C.



THERMAL CUTOUT
If the water temperature exceeds the preset level, the thermal cut-out cuts off the power supply to assure safety.



SAFETY VALVE
The safety valve is designed to automatically relieve pressure and discharge water in case the pressure overshoots the preset limits.



INSULATION FOAM 50mm,
50mm boonryeok excellent heat dissipation effect of preventing the other products with polyurethane insulation the more excellent.



STRESS TEST
A. O. Smith to ensure the best quality self-testing 21kgf / cm2.

SPECIFICATIONS

MODEL	EES 30	EES 40	EES 50	EES 80	EES 120	
Volume [L]	120	150	190	300	455	
Power [W]	6000					
Voltage/Frequency [V/Hz]	220V/50Hz					
Rated water pressure [Bar]	8					
Form of water inlet & outlet	Top inlet / Top outlet					
Dimensions	A [mm]	530	530	520	620	720
	B [mm]	940	1115	1395	1470	1635
Net Weight [kg]	43	53	60	94	153	

