



3-Wire, 4" Submersible Well Pumps



**For Residential Water Systems
or Agricultural Applications**

Pumps to depth of 400'

High Performance

Proven floating stack impeller design for sand resistance and reduced sand locking

Durable Construction

Stainless steel pump and motor housing



Control Box Included

1/2 HP – 1 HP 14-26.2 GPM

PERFORMANCE																	
MODEL/ UPC	HP	GPM SERIES	VOLTS	GALLONS PER MINUTE PUMPED AT DIFFERENT DEPTHS TO WATER IN FEET											DISCHARGE	CARTON DIMS. (IN INCHES)	WEIGHT (LBS.)
				20'	40'	60'	80'	100'	150'	200'	250'	300'	350'	400'			
FP3212 022315101944	1/2	10	230	13.2	12.2	10.9	9.6	8.1	2	-	-	-	-	-	1-1/4"	21 x 12.5 x 12.3	25
FP3222 022315101951	3/4	10	230	14.8	14.2	13.4	12.6	11.7	8.8	5.2	-	-	-	-	1-1/4"	6 x 4.6 x 40	28
FP3232 022315101968	1	10	230	-	-	14.7	14	13.4	11.7	9.7	7.3	4.4	-	-	1-1/4"	6 x 4.6 x 40	31
FP3242 022315100916	1-1/2	10	230	-	-	-	-	14.9	13.8	12.5	11.2	10.4	7.9	5.8	1-1/4"	6 x 4.5 x 49	41
FP3332 022315101975	1	20	230	27	24.5	22.0	19.4	16.8	2.6	-	-	-	-	-	1-1/4"	5 x 4.5 x 43.5	30
FP3342 022315163294	1-1/2	20	230	-	-	26.2	24.3	22.3	17.3	8	-	-	-	-	1-1/4"	48.9 x 5.8 x 4.6	41

*All performances shown in gallons per minute at 40 PSI discharge pressure at the top of the well.

Optimal pump performance

Includes: Control box