

FLAT CAP SLIM LINE SERIES FILTER HOUSINGS

AN EXCELLENT CHOICE FOR LOW-FLOW APPLICATIONS & WHEN SPACE AND CHEMICAL COMPATIBILITY ARE PRIMARY CONCERNS



Pentair Flat Cap Slim Line[§] Filter Housings are manufactured of a durable polypropylene or clear Styrene-Acrylonitrile (SAN). These housings are available in 10" lengths, while the caps are available with 1/4" or 1/2" NPT connections.

Opaque Flat Cap Slim Line housings, molded from rugged reinforced polypropylene, offer outstanding chemical compatibility and are ideal for use in a variety of low-flow applications. These applications include undersink and countertop residential filtration, pre- and post-reverse osmosis filtration, recreational vehicle filtration, food service and humidifying systems.

Clear Flat Cap Slim Line housings offer on-site examination of flow, performance, and cartridge life. They are also ideal for a variety of applications.

FEATURES/BENEFITS

Slim design reduces space required for installation without sacrificing capacity

Available in 10" length

Available in clear or opaque sumps

Leak-proof seal

SPECIFICATIONS

Housing - Polypropylene (opaque) or Styrene Acrylonitrile (clear)

Cap – Reinforced Polypropylene Button Assembly – 300 Series stainless steel, EPDM, and polypropylene

O-Ring - Buna-N

Temperature Rating – 40-125°F (4.4-51.7°C)

Maximum Pressure – 125 psi (8.6 bar)



The 158739 is Tested and Certified by NSF International to NSF/ANSI Standard 42 for material and structural integrity requirements.

SPECIFICATIONS AND PERFORMANCE

| PART # | DESCRIPTION | MAXIMUM DIMENSIONS | INITIAL ΔP (PSI) @ FLOW RATE (GPM) |
|---------|--|-------------------------------|------------------------------------|
| 158739* | 1/4" #10 Flat Cap Slim Line White/White w/o PR | 12.36" x 4.63" (314 x 118 mm) | 1 psi @ 10 gpm (0.07 bar @ 38 Lpm) |
| 158784 | 1/4" #10 Flat Cap Slim Line White/Clear w/o PR | 12.36" x 4.63" (314 x 118 mm) | 1 psi @ 10 gpm (0.07 bar @ 38 Lpm) |
| 158785 | 1/2" #10 Flat Cap Slim Line White/White w/o PR | 12.36" x 4.63" (314 x 118 mm) | 1 psi @ 10 gpm (0.07 bar @ 38 Lpm) |

CAUTION: Protect against freezing to prevent cracking of the filter and water leakage. *WQA certified

ACCESSORIES

| PART# | DESCRIPTION |
|-----------|--|
| 150539 | SW-1A for Slim Line |
| 158095 | Viton #237 for Slim Line |
| 158096 | Silicone #237 for Slim Line |
| 244047 | SL-ZP Kit - Zinc Plated Bracket for Slim Line |
| 357638 | SL-SS - Stainless Steel Bracket ONLY for Slim Line |
| 357644 | SL-SS Kit - Stainless Steel Bracket for Slim Line |
| 244046-00 | SL-ZP - Zinc Plated Bracket ONLY for Slim Line |
| 244627-02 | Two-Housing System Bracket |

