Cast Iron

Shallow Well Jet Pumps

With Built-in Pressure Switch

Rugged Cast Iron Construction

For heavy-duty applications

Reliable Performance

At depths to water of 25' or less

Ready-to-Install Motor

Operates at 115V

Self-Priming After Pump Housing Is Initially Filled

Check valve or foot valve required, sold separately



3/4 HP 8.3 GPM FP4107

1/2 HP 5.6 GPM FP4105

PERFORMAN	MAX	V017405	PRESSURE SWITCH							
DEPTH TO WATER	0,	5'	10'	15'	20'	25'	PRESSURE SHUTOFF	VOLTAGE	ON	OFF
FP4107	8.3	7.8	7.3	6.7	6.1	5.0	74 PSI	115	30	50
FP4105	5.6	5.1	4.5	4.1	3.5	3.1	63 PSI	115	30	50

All performances shown in gallons per minute at 40 PSI discharge pressure.

MODEL	WARRANTY	UPC	CARTON DIMENSIONS	PALLET QTY.	WEIGHT	
FP4107	1 YEAR	022315322486	15.200" x 9.4" x 11"	27	23.55 LBS.	
FP4105	1 YEAR	022315176225	15.200" x 9.4" x 11"	27	24.25 LBS.	



Includes

Factory-installed 30/50 preset pressure switch, detailed owner's manual