

Thermoplastic Convertible Jet Pumps

For Deep or Shallow Wells

Superior Performance

At depths to water of 110' or less

Fiberglass-Reinforced Thermoplastic Pump Housing

For the highest corrosion resistance

Heavy-Duty Dual-Voltage Motor

3/4 HP & 1 HP preset at 230V
1/2 HP preset at 115V;

Self-Priming After Pump Housing Is Initially Filled

Foot valve included with Jet Kit, sold separately

Prewired Pressure Switch

Preset for 30/50 PSI operation

Built-in Pressure Regulator

Includes:

Factory-installed 30 PSI gauge, preset pressure switch, detailed owner's manual



1 HP	9 GPM	FP4332	3/4 HP	7.5 GPM	FP4322	1/2 HP	5.9 GPM	FP4312
-------------	--------------	---------------	---------------	----------------	---------------	---------------	----------------	---------------

PERFORMANCE																								
MODEL/ UPC	HP	GPM	VOLTS	GALLONS PER MINUTE PUMPED AT DIFFERENT DEPTHS TO WATER IN FEET												PRESS. SHUTOFF AT MAX DEPTH	JET KIT	PRESS. SWITCH		CARTON DIMS. (INCHES)	WT. (LBS.)			
				5'	10'	15'	20'	30'	40'	50'	60'	70'	80'	90'	100'			110'	ON			OFF		
FP4332 022315100688	1	9	230/115																					
Deep Well with 4" dia. casing or larger																								
Deep Well with 2" dia. casing																								
Shallow Well of 25' or less																								
FP4322 022315100671	3/4	7.5	230/115																					
Deep Well with 4" dia. casing or larger																								
Deep Well with 2" dia. casing																								
Shallow Well of 25' or less																								
FP4312 022315100664	1/2	5.9	230/115																					
Deep Well with 4" dia. casing or larger																								
Deep Well with 2" dia. casing																								
Shallow Well of 25' or less																								

All performances shown in gallons per minute at 40 PSI discharge pressure.