




JET PUMP & TANK SYSTEMS



MODEL 2802E 3/4 HP
MODEL 2800E 1/2 HP

- Shallow well pump
- Reliable performance at 25' depth to water or less
- Ready to Install 115 volt motor
- Pressure switch pre-wired to 30-50 PSI pressure setting
- Pump tank system pre-assembled and ready to install
- 7 gallon pre-charged diaphragm tank
- 1" NPT suction and discharge pipe size
- Excellent self-priming capability after pump housing is initially filled (Check or foot valve required)



PERFORMANCE

Model	HP	Warranty	Voltage	Amps	Pressure Switch		GPM Pumped at Different Depths to Water*					Pressure Shut-off
					On	Off	5'	10'	15'	20'	25'	
2802E	3/4	1-year	115	8.6	30	50	7.8	7.3	6.7	6.1	5.0	74 PSI
2800E	1/2	1-year	115	7.2	30	50	5.1	4.5	4.1	3.5	3.1	63 PSI

*All performances shown in gallons per minute at 40 PSI (pound per square inch) discharge pressure at top of well.

ORDERING INFORMATION

Model	UPC	Carton (L x W x H)	Cube	Pallet Qty.	Weight
2802E	0 17561 91164 5	20.75" x 12.25" x 23"	3.383	18	41.45 lbs.
2800E	0 17561 91162 1	12" x 20.5" x 23"	3.27	18	37.5 lbs.