




SPRINKLER PUMP

MODEL 3420P 2 HP
MODEL 3415P 1-1/2 HP
MODEL 3410P 1 HP



- Superior performance at depths to water of 20' or less
- Fiberglass reinforced thermoplastic pump housing for the highest corrosion resistance
- Ready to install 230 volt, heavy-duty motor, see manual for 115 volt conversion
- Self priming after pump housing is initially filled, protects against overheating



PERFORMANCE

Model	HP	Warranty	Motor Voltage	NPT Pipe Size		Distance of Pump Above Water	Discharge Pressure PSI								
				Suction	Discharge		10	15	20	25	30	35	40	45	50
3420P	2	1-year	115/230	2"	2"	5 ft.	69	64	59	53	47	40	34	24	14
						10 ft.	67	62	56	50	45	38	30	18	7
						15 ft.	65	60	54	48	42	35	27	13	—
						20 ft.	62	57	52	46	40	32	23	10	—
3415P	1-1/2	1-year	115/230	1-1/2"	1-1/2"	5 ft.	67	66	61	55	48	39	33	18	—
						10 ft.	61	58	56	52	45	37	27	14	—
						15 ft.	56	55	54	51	44	35	20	8	—
						20 ft.	46	45	44	43	37	28	11	—	—
3410P	1	1-year	115/230	1-1/2"	1-1/2"	5 ft.	55	51	45	38	31	23	17	—	—
						10 ft.	49	46	42	35	28	19	13	—	—
						15 ft.	48	45	39	32	24	16	8	—	—
						20 ft.	45	44	37	29	20	11	—	—	—

ORDERING INFORMATION

Model	UPC	Carton (L x W x H)	Cube	Pallet Qty.	Weight
3420P	0 22315 31584 6	21.563" x 12.813" x 15.375"	2.458	18	41.2 lbs.
3415P	0 17561 91169 0	21.563" x 12.813" x 15.375"	2.458	18	35.0 lbs.
3410P	0 22315 31583 9	21.563" x 12.813" x 15.375"	2.458	18	30.6 lbs.