ANTI-FLOTATION COLLAR 1 1/4" BALL VALVE, PVC TRUE UNION, BLOCKED TYPE CONDUIT FLANGE DISCHARGE FLANGE, SST 1–1/4" – INSIDE BASIN 1–1/2" NPT– OUTSIDE BASIN 45° FLOAT BRACKET 53 SST SIMPLEX JUNCTION BOX, STRUCT. PLASTIC (HAZARDOUS LOCATION JUNCTION BOX FOR HPGX) 2" NPT CONDUIT FLANGE STRUCT. PLASTIC 24" BASIN COVER, STRUCTURAL PLASTIC 10" RAIL SUPPORT, SST STD. LIFTOUT CHAIN, 1/4" SST Ö ANTI-SIPHON VALVE, BRASS W/ ABS SCREEN 1 1/4" TRUE UNION BALL VALVE, PVC 4" ADAPTFLEX INLET (PLASTIC EXTENSION HANDLE) HUB (FIELD INSTALLED) ð DISCHARGE FLANGE, SST 1-1/4" NPT INSIDE BASIN 1-1/2" NPT OUTSIDE BASIN INVERT HIGH WATER "ALARM" LEVEL GUIDE RAILS, 1" SST PIPE 台 5'.6'.7'.8' HA A PUMP "ON" LEVEL 24" DIA Basin Heights 36" FIBERGLASS BASIN 1-1/4" PIPE. SCH. 80 PVC GRINDER PUMP -PUMP "OFF" LEVEL LIFTOUT W/CHECK VALVE, 24" DIA. CAST IRON, SST GUIDE PLATE NOTE: 30" Basin minimum requirement for HPGX

TL-PRO – SIMPLEX FIBERGLASS LOW PRESSURE SEWER SYSTEM