

HYDROMATIC® SHEF30 SUBMERSIBLE EFFLUENT PUMPS

Effluent Septic Tank

Automatic operation features easily adjustable, wide-angle float switch with a piggyback plug-in arrangement that allows for simple conversion to manual operation. Special inlet design allows pump to handle 3/4" solids. Cast iron body and an oil-filled motor provide superior cooling characteristics for longer pump life. Motor windings contain automatic thermal overload protection. Energy efficient .3 HP motor pumps up to 35 GPM at 10' total dynamic head. Discharge is 1-1/2" N.P.T.



May be operated manually
or automatically with a
piggyback switch.



HYDROMATIC® SHEF30 SUBMERSIBLE EFFLUENT PUMP


Pump Characteristics

Pump/Motor Unit	Submersible
Automatic Model	SHEF30A1
Manual Model	SHEF30 MI
Horsepower	.30
Full Load Amps	8.0
Motor Type	Shaded Pole (4 pole)
R.P.M.	1550
Phase Ø	1
Voltage	115
Hertz	60
Temperature	120°F Ambient
NEMA Design	A
Insulation	Class B
Discharge Size	1-1/2" NPT (38mm)
Solids Handling	3/4" (19mm)
Unit Weight	30 lbs.
Power Cord	18/3, SJTW, 20' std.


Materials of Construction

Part Name	Material
Handle	Stainless Steel
Lubricating Oil	Dielectric Oil
Motor Housing	Cast Iron
Pump Volute	Cast Iron
Shaft	Steel
Mechanical Shaft Seal	Seal Faces: Carbon/Ceramic Seal Body: Anodized Steel Spring: Stainless Steel Belows: Buna-N
Impeller	Engineered Thermoplastic
Upper Bearing	Cast Iron Sleeve
Lower Bearing	Single Row Ball Bearing
Legs	Engineered Thermoplastic
Fasteners	Stainless Steel

Performance Data



Dimensional Data



All dimensions in inches. Component dimensions may vary $\pm 1/8$ inch. Dimensional data not for construction purpose unless certified. Dimensions and weights are approximate. On/Off level adjustable. We reserve the right to make revisions to our product and their specifications without notice.



USA
293 WRIGHT STREET, DELAVAN, WI 53115 WWW.HYDROMATIC.COM
PH: 888-957-8677 ORDERS FAX: 800-426-9446

CANADA
269 TRILLIUM DRIVE, KITCHENER, ONTARIO, CANADA N2G 4W5
PH: 519-896-2163 ORDERS FAX: 519-896-6337

Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.