

Thermoplastic Shallow Well Jet Pumps

With Built-in Pressure Switch

Superior Performance

At depths to water of 25' or less

Fiberglass-Reinforced Thermoplastic Pump Housing

For the highest corrosion-resistance

Heavy-Duty Dual-Voltage Motor

1/2 HP preset at 115V; 3/4 HP & 1 HP preset at 230V

Self-Priming After Pump Housing Is Initially Filled

Check valve or foot valve required, sold separately



1 HP 18 GPM FP4032	3/4 HP 12 GPM FP4022	1/2 HP 8 GPM FP4012
------------------------------	--------------------------------	-------------------------------

PERFORMANCE (GPM)							MAX PRESSURE SHUTOFF	VOLTAGE	PRESS. SWITCH	
DEPTH TO WATER	0'	5'	10'	15'	20'	25'			ON	OFF
FP4032	18	16.4	16.1	14.1	12.0	8.1	67 PSI	115/230	30	50
FP4022	12	10.3	9.7	8.2	7.1	5.1	78 PSI	115/230	30	50
FP4012	8	7.4	6.4	6.1	5.1	4.0	77 PSI	115/230	30	50

All performances shown in gallons per minute at 40 PSI discharge pressure.

MODEL	WARRANTY	UPC	CARTON DIMENSIONS	PALLET QTY.	WEIGHT
FP4032	1 YEAR	022315315150	22.813" x 11.063" x 10.5"	24	29.15 LBS.
FP4022	1 YEAR	022315100589	22.813" x 11.063" x 10.5"	24	26.9 LBS.
FP4012	1 YEAR	022315100572	22.813" x 11.063" x 10.5"	24	23 LBS.

Includes:

Factory-installed 30/50 preset pressure switch, detailed owner's manual

